



OPTIONS:

- ① Imm.length/L1/mm  
160mm  
250mm  
400mm
- ② Sheath dia./wallthickn./mm  
ø8x1  
ø9x1
- ③ Mounting thread  
1/2" BSP  
3/4" BSP  
1" BSP
- ④ Number of conductors  
2 cond.  
3 cond.  
4 cond.  
Prepared for 3 cond. transmitter  
Prepared for 4 cond. transmitter
- ⑤ Temperature range  
-50 / +260°C  
-50 / +500°C  
-50 / +600°C  
-50 / +400°C (w.vibrations)
- ⑥ Tolerance Class/DIN  
Cl.A : ±0.15°C  
Cl.B : ±0.3°C  
1/3 DIN : ±0.1°C  
1/6 DIN : ±0.05°C
- ⑦ Resistance in ohms at 0  
100  
500  
1000
- ⑧ Number of elements  
1xPt  
2xPt

Note:

Options 1-8 must be specified when ordering  
MICROMATIC Type BF—sensor

ELEMENT: 1/2 PT 100 (500/1000)— 3 WIRE/4WIRE

ISSUED BY	WEEK	PRODUCT CODE	FILE	INSTALLATION DRAWING TITLE
GSP-AJ	0204	REX	ACAD	MICROMATIC Temp. sensor BF—type
APPROVED BY	WEEK	ORIGINAL DWG NO.	SCALE	Dimensional drawing
GSP	0204	9261 090-151	—	
ROSEMOUNT®		DOC TYPE	DWG NO.	ISSUE SHEET
Tank Gauging		2	9261 090-151	2 1/1

THE COMPANY ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE INFORMATION CONTAINED HEREIN. THE USER SHALL BE RESPONSIBLE FOR VERIFYING THE ACCURACY OF THE INFORMATION CONTAINED HEREIN. THE COMPANY SHALL NOT BE HELD RESPONSIBLE FOR ANY DAMAGE OR LOSS OF PROFITS OR BUSINESS INTERRUPTIONS RESULTING FROM THE USE OF THE INFORMATION CONTAINED HEREIN. THE COMPANY SHALL NOT BE HELD RESPONSIBLE FOR ANY DAMAGE OR LOSS OF PROFITS OR BUSINESS INTERRUPTIONS RESULTING FROM THE USE OF THE INFORMATION CONTAINED HEREIN.