



OPTIONS:

- ① Imm. length /L1 /mm
min. 100mm
max. 2000mm
- ② Sheath dia./wallthickn./mm
ø9
- ③ Mounting thread
1/2"NPT
1/2"BSP
3/8"BSP
- ④ Number of conductors
3 cond.
4 cond.
Prepared for 3 cond. transmitter
Prepared for 4 cond. transmitter
- ⑤ Temperature range
-50 / +500°C
- ⑥ Tolerance Class/DIN
Cl.A : ±0.15°C
Cl.B : ±0.3°C
1/3 DIN : ±0.1°C
1/6 DIN : ±0.05°C
- ⑦ Resistance in ohms at 0°C
100
- ⑧ Number of elements
1xPt
2xPt on special request
- ⑨ Cable outlet
1/2"NPT
1/2"BSP



Note:

Options 1-9 must be specified when ordering
MICROMATIC Type OPE—sensor

ISSUED BY	WEEK	PRODUCT CODE	FILE	INSTALLATION DRAWING TITLE
GSP-AJ	0220	REX	ACAD	MICROMATIC SINGLE SPOT
APPROVED BY	WEEK	ORIGINAL DWG NO.	SCALE	TEMP. SENSOR OPE
GSP	0220	9261 090-153	-	
ROSEMOUNT®		DOC TYPE	DWG NO.	ISSUE
Tank Gauging		2	9261 090-153	2
				1/1

THE COMPANY ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE INFORMATION CONTAINED HEREIN. THE INFORMATION IS PROVIDED AS IS WITHOUT WARRANTY OF ANY KIND. THE USER SHALL BE RESPONSIBLE FOR THE ACCURACY OF THE INFORMATION. THE COMPANY SHALL NOT BE HELD RESPONSIBLE FOR ANY DAMAGES, INCLUDING CONSEQUENTIAL DAMAGES, ARISING FROM THE USE OF THE INFORMATION. ROSEMOUNT TANK GAUGING AB, SWEDEN.