



- ① THE ANCHOR WEIGHT MUST BE KEPT CLEAR INSIDE THE PIPE.
- ② FOR CLEAN PRODUCTS ONLY. MIN PIPE SIZE FOR HIGH VISCOSITY PRODUCTS IS 3" SCH 40-80. THE WLS IS NOT RECOMMENDED TO BE INSTALLED IN STILL PIPE FOR WAXY CRUDE OILS.

ISSUED BY	WEEK	PRODUCT CODE	FILE	ACAD	INSTALLATION DRAWING TITLE	ISSUE	SHEET
GSP-AJ	0243	REX	ACAD	MECH. INSTALLATION DWG	2	2	1/1
APPROVED BY	WEEK	ORIGINAL DWG NO.	SCALE	WLS IN STILL PIPE	DOC TYPE	DWG NO.	
GSP	0243	9261 090-154	-		2	9261 090-154	

ROSEMOUNT
Tank Gauging

1 ST ANGLE

THE COMPANY ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE DATA WILL BE OBTAINED USING THE ROSEMOUNT TANK GAUGING SYSTEM WITHOUT OUR AUTHORIZATION OR ENDORSEMENT TO THE KNOWLEDGE OF A THIRD PARTY. CONSULTATION WITH ROSEMOUNT, ROSEMOUNT TANK GAUGING AB, SWEDEN.